

Technical Data Sheet

Sealer Strippa



Product	Sealer Strippa is a methylene chloride based Heavy duty paint and sealer stripper
Usage	For stripping old concrete sealer, enamel, varnish and lacquer from concrete, wood and metal.
Benefits	Slow drying, Non Corrosive and Non Flammable
Coverage	Approximately 3/4 sq mtrs per litre. May vary according to thickness of coating to be removed.
Package	20 lt Pail.
Storage	<ul style="list-style-type: none">• Store in cool dry well ventilated area, and out of direct sunlight.• Store away from sources of ignition.
Shelf Life	Approximately 12 months, providing stores correctly and unopened
Handling	<ul style="list-style-type: none">• Manual handling without due care could result in personal injury.• Avoid contact with skin and eyes.• Avoid breathing vapours.• Wear suitable protective equipment.
Equipment	Stiff Broom, Scraper.
Properties	Appearance: Thick translucent liquid Odour: Pungent odour
Application	<p>Surface must be completely clean and dry prior to starting. Mask up any fences, walls, and posts etc. using plastic to prevent damage. It may also be necessary to mask any garden plants to prevent accidental damage during the pressure washing process.</p> <p>Apply the solution at the lowest point which will leave higher areas dry after water blasting. Working on 10 to 15 sq mtrs at one time. Apply a thick coating of the solution onto the surface to be stripped. Do not apply a thin coat as this will not be enough to strip the sealer. Leave for 5 to 10 minutes to penetrate.</p> <p>Scrub the surface with a stiff broom to emulsify the sealer. Scrape off excess before water blasting. Do not allow the surface to dry before water blasting. Water blast the surface thoroughly.</p> <p>If any thick white or coloured sealer residue remains scrub with stripper then water blast a second time. Then remove all old sealer and the sealer stripper. If the area is to be re-sealed follow instructions for sealing of unsealed surfaces.</p>

Disclaimer

The information given is based on our knowledge of the health and safety data of this product, at the time of publication, and is given in good faith. The attention of the user is drawn to the possible risks incurred by using the product for any purpose other than that for which it was intended. If clarification or further information is needed to enable appropriate risk assessment, the user should contact Bescon Industries. Responsibility for products sold is subject to our standard terms and conditions sent to customers. No liability whatsoever can be accepted with regard to the handling, processing or use of the product concerned which, in all cases, shall be accordance with the appropriate regulations and / or legislation.