

Stencil Paving - Finta Brick™

Application Guidelines



System

This unique form of paving allows you to have the grouted look of Cobblestone and Bricks without the added expense of having it grouted. This system incorporates the use of Stencils, Coloured Surface Hardeners, Texture Rollers and Sealers. These will enable you to have an endless choice of colours and pattern, thus adding value and charm to your property.

Precautions

Prior to the application it is advisable to protect walls and structure to avoid risk of possible staining. Ensure all excess contaminations do not enter into waterways drains or other storm water facilities.

Application

1. Place concrete in the traditional manner, allow excess bleed water to evaporate from surface and commence laying stencil. The Stencil should be cut slightly longer to allow for lining up and trimming. It is advisable to do this before placing of concrete has commenced, to save time. Use a Textured Roller or Fresno to place the stencil flush with the surface of the concrete, this is to be done before laying the next row. Take care not to bury the stencil in the concrete. Trim edge's approximately 3 mm short of form work to allow room for an edger.

2. Apply TuffTop™ Coloured Surface hardener and finish to desired texture. Do not over trowel. When Texturing is completed, remove stencil by pulling straight up, taking care. Expansion joints may be cut and rinsed the following day.

3. Allow to dry and apply Staseal™ Sealer as recommended on the Data Sheet or label, to protect the surface and enhance the colour. Same day sealing is recommended to reduce the risk of efflorescence

Products

Stencil, Statop or Tufftop coloured surface hardener, Sealer.

Equipment

Hopper gun, Hopper gun stand, Compressor, Drill with stirrer, Sealer broom or Airless spray gun.

Note

These techniques are only a guideline and may vary according to site conditions.